

QM10HB-2H

DRIVE USE FOR HIGH POWER TRANSISTOR
INSULATED TYPE

QM10HB-2H



- **I_C** Collector current **10A**
- **V_{CEX}** Collector-emitter voltage **1000V**
- **h_{FE}** DC current gain **5**
- **Insulated Type**
- **UL Recognized**

Yellow Card No. E80276 (N)


File No. E80271

APPLICATION

Base driver for High voltage transistor modules

OUTLINE DRAWING & CIRCUIT DIAGRAM

Dimensions in mm



QM10HB-2H

DRIVE USE FOR HIGH POWER TRANSISTOR
INSULATED TYPE

ABSOLUTE MAXIMUM RATINGS (Tj=25°C, unless otherwise noted)

Symbol	Parameter	Conditions	Ratings	Unit
VCEX (SUS)	Collector-emitter voltage	IC=1A, VEB=2V	1000	V
VCEX	Collector-emitter voltage	VEB=2V	1000	V
VCBO	Collector-base voltage	Emitter open	1000	V
VEBO	Emitter-base voltage	Collector open	7	V
IC	Collector current	DC	10	A
PC	Collector dissipation	Tc=25°C	100	W
IB	Base current	DC	2	A
Tj	Junction temperature		-40~+150	°C
Tstg	Storage temperature		-40~+125	°C
Viso	Isolation voltage	Charged part to case, AC for 1 minute	2500	V
—	Mounting torque	Mounting screw M3	0.59~0.98	N·m
—	Weight	Typical value	6~10	kg·cm
—	Weight	Typical value	40	g

ELECTRICAL CHARACTERISTICS (Tj=25°C, unless otherwise noted)


Symbol	Parameter	Test conditions	Limits			Unit
			Min.	Typ.	Max.	
ICEX	Collector cutoff current	VCE=1000V, VEB=2V	—	—	1.0	mA
ICBO	Collector cutoff current	VCB=1000V, Emitter open	—	—	1.0	mA
IEBO	Emitter cutoff current	VEB=7V	—	—	150	mA
VCE (sat)	Collector-emitter saturation voltage	IC=5A, IB=1A	—	—	1.0	V
VBE (sat)	Base-emitter saturation voltage		—	—	1.5	V
hFE	DC current gain	IC=5A, VCE=1V	5	—	—	—
ton	Switching time	VCC=600V, IC=5A, IB1=-IB2=1A	—	—	1.5	μs
ts			—	—	7.0	μs
tf			—	—	2.0	μs
Rth (j-c) Q	Thermal resistance (junction to case)	Transistor part	—	—	1.2	°C/W
Rth (c-f)	Contact thermal resistance (case to fin)	Conductive grease applied	—	—	0.4	°C/W

QM10HB-2H


DRIVE USE FOR HIGH POWER TRANSISTOR
INSULATED TYPE

PERFORMANCE CURVES


COMMON EMITTER OUTPUT
CHARACTERISTICS (TYPICAL)



SATURATION VOLTAGE
CHARACTERISTICS (TYPICAL)



DC CURRENT GAIN VS.
COLLECTOR CURRENT (TYPICAL)



SWITCHING TIME VS. COLLECTOR
CURRENT (TYPICAL)

